

# CELL PHONE INSTRUCTIONS

pfi ver. 10/10/2003

One cell phone each has been given to the CAS watch, the OC, and the Siemens Power Room Watch so that they can provide back up for MCR for “critical” alarms.

phone #	e-mail	s/n	owner
631-807-4933	6318074933@vtext.com	11238530512	OC
631-921-1746	6319211746@vtext.com	11238225756	MMPS
631-786-5911	6317865911@vtext.com	11236541828	CAS

The primary purpose of the cell phone is to receive alarms in the form of e-mails generated by the Alarm Display Task. We will limit the list of possible alarms that will be sent to **bgisCtrl** (brahms alarms), **pgisCtrl** (PHENIX alarms), **sgisCtrl** (STAR alarms), **odh** (summary alarms generated by the PASS system), **grndFaultCh** (substation ground faults), **bldgTempCh** (building high temperature alarms), **util** (equipment high temperature alarms), **LBC** (BLIP alarms), and **PR** (pump room/water systems alarms). Ingrassia/Sampson manage the list and turn off alarms for non-operating systems.

## THINGS WE ASSUME YOU KNOW HOW TO DO

- Charge the battery when it is low
- Make a phone call (do not abuse the privilege)

## THINGS YOU SHOULD LEARN HOW TO DO (read instructions)

- Make use of the GPS feature so you can be located in an emergency

## THINGS YOU NEED TO KNOW:

- **Turn the unit on/off**
  1. Depress and hold down the key with the picture of the red phone handset
- **How to read an alarm**
  1. Observe the envelope icon on the top line of the lcd display
  2. Press the key with the picture of the envelope on it (left of CLR button)
  3. Move cursor down to “Inbox” using circular joystick in center of keypad
  4. Move cursor right using joystick
  5. Move cursor right a second time using joystick – see “new/old text”
  6. Move cursor down as many times as needed to read the message
  7. Press CLR button repeatedly to return to initial display
- **How to erase an alarm**
  1. Press the key with the picture of the envelope on it (left of CLR button)
  2. Move cursor down to “Inbox” using circular joystick in center of keypad
  3. Move cursor right using joystick
  4. Move cursor right a second time using joystick – see “new/old text”
  5. Press “|” key (left of joystick) for “Option”
  6. Move cursor down to “Erase” using joystick
  7. Move cursor right using joystick
  8. Move cursor over YES
  9. Press “||” button for OK
  10. Press CLR button repeatedly to return to initial display

## NOTE:

The mail buffer holds only 30 messages – you need to keep the buffer clear.

IF after three days a message is not read then it is deleted from the buffer by Verizon